

# EF401 Touch Mobile Computer



# Super Compact, Super Smart

Powerful Enterprise Functionalities  
In a Pocket-sized Design

Android 7 or 9;  
Upgradeable to Android

IP67

1.2m

MIL STD-810G

11



## • Features & Benefits

### Ultimate Performance

The reliable and powerful 2.0 GHz Octa-core processor ensures higher level of performance that can run multiple applications with minimum power consumption. Running Android 7 or 9; Upgradeable to Android 11, the EF401 provides ultimate on-the-go productivity packed with enterprise-focused features.

### Fast, Stable Connectivity

EF401 provides the fastest, reliable wireless connections with support for the fastest Wi-Fi and 4G LTE, enabling workers to stay connected whenever, wherever they need.

### Glove & Wet Touch Panel

Can be operated with finger, or gloves even if they are wet. Slim form factor and non-slip grip texture ensures easy one-handed operation.

### Enterprise-Class Durability

EF401 incorporates TankSmith® Technology to withstand drops and shocks, protecting the device from water, dust, and dirt. The Corning® Gorilla® Glass touch panel is resistant to scratches and smudges.

### Allows Continuous Work Throughout the Day

Capability of multi-tasking with minimal power consumption ensures best-in-class battery time. (PowerManager™ Smart Battery Available-Optional)

### The Most Advanced Scanning

With the advanced scanning technology, workers can capture 1D and 2D barcodes as well as dirty and damaged barcodes quickly and accurately.

## • Industry & Applications

### Retail – Associates

- Price checks / changes / audits
- Inventory management
- Financial / loyalty management
- Voice communications
- Buy online, pick up in store

### Field Service

- Task management
- Competitive surveys
- Sales / order tracking
- Order / service automation
- Route optimization

### Manufacturing

- Asset management
- Building maintenance
- Management of product information
- Supplier management

### Retail – Managers

- Workforce management
- Merchandising
- Promotion compliance
- Planogram management

### Restaurant & Hospitality

- Order taking
- Mobile payment
- Inventory checks
- Workforce management
- Financial / loyalty applications

### Healthcare

- Patient identity management
- Data management / collection
- Staff collaboration
- Workflow efficiency

### T&L

- Proof of delivery
- Direct Store Delivery(DSD)
- Route Accounting
- Fleet Management
- Delivery tracking

### Public Safety

- Alternate to two-way radio
- Data collection
- ID validation / ticketing
- Records query
- Documentation

## • Enterprise-Focused Features Accessories

1 Slot  
Charging Cradle



4 Slot  
Charging Cradle



Vehicle Cradle



6 Slot  
Battery  
Charger\*



Smart Battery  
& Cover



UHF RFID Reader  
(w/RFR900)



Leather Holster



Wearable  
Package\*

Wristband + Trigger Ring



Trigger Handle\*



\* Remarkd accessories are supplied under the terms and conditions.  
Please visit our official website or contact to our sales representative for availability of the remarked accessories.

# Specification

## PERFORMANCE CHARACTERISTICS

|                  |  |
|------------------|--|
| CPU              | 2.0 GHz Octa Core Processor                  |
| Operating System | Android 7 or 9;<br>Upgradeable to Android 11 |
| Memory           | 2GB RAM / 16GB Flash                         |

## PHYSICAL CHARACTERISTICS

|                        |  |
|------------------------|--|
| Dimensions (L x W x D) | 136.3 x 68 x 15.9 mm 5.37 x 2.68 x 0.63 in.  |
| Weight                 | 7.05 oz. 200g (with standard battery)<br>8.82 oz. 250g (with extended battery)   |
| Display                | 4.0 inch, WVGA (800 X 480)   |
| Imager Window          | Corning® Gorilla® Glass 3  |
| Touchpanel             | Capacitive multi-touch / Glove, Wet, Stylus  |
| Backlight              | LED backlight  |
| Power                  | User Replaceable Battery<br>Standard: 3.8V 2860 mAh<br>Extended: 3.8V 5720 mAh<br>Smart battery : 3.8V 2860 mAh (Optional) |
| Quick Charging         | 2.2 hours, Normal battery with charging cradle<br>3.8 hours, Extended battery with charging cradle                         |
| Expansion Slot         | MicroSD 32GB SDHC, up to 128GB SDXC  |
| SIM / SAM              | 1 Micro SIM  |
| Interface              | 1 x Micro USB<br>Docking Connector (USB 2.0)<br>Rear 10-pin Connector (Optional)   |
| Notification           | Audible tone; Multi-color LEDs; Vibration  |
| Keypad                 | On-screen keypad,<br>Dual-action side scan triggers,<br>Volume Up / Down, Power Button                                     |
| Voice and Audio        | Dual noise-cancelling<br>microphones; High-quality speaker<br>phone; 3.5mm headset jack                                    |
| PTT Hot Key            | Support  |

## WIRELESS WAN DATA AND VOICE COMMUNICATIONS

|                      |   |
|----------------------|---|
| Radio Frequency Band | (Optional)<br>Worldwide<br>• LTE : 1/2/3/4/5/7/8/20<br>• UMTS/HSPA/HSPA+ : 1/2/3/4/5/8<br>• GSM/GPRS/EDGE : 850/900/1800/1900<br>Americas<br>• LTE : 1/2/3/4/5/8/17<br>• UMTS/HSPA/HSPA+ : 1/2/3/4/5/8<br>• GSM/GPRS/EDGE : 850/900/1800/1900 |
| GPS                  | (for WWAN only)<br>A-GPS, GLONASS, BEIDOU (Default)   |

## WIRELESS LAN

|                         |   |
|-------------------------|---|
| Radio                   | 802.11 a/b/g/n/ac/d/r/h/i/v/k/w   |
| Data Rates              | 5GHz: 802.11a/n/ac – up to 500 Mbps;<br>2.4GHz: 802.11b/g/n – up to 144Mbps   |
| Security and Encryption | WEP (40 or 104 bit);<br>WPA/WPA2 Personal (TKIP, and AES);<br>WPA/WPA2 Enterprise (TKIP and AES)<br>– EAPTTLS (PAP, MSCHAP, MSCHAPv2),<br>EAP-TLS, PEAPv0-MSCHAPv2, PEAPv1-<br>EAP-GTC and LEAP |

## WIRELESS PAN

|           |                            |
|-----------|----------------------------|
| Bluetooth | Bluetooth 4.2 BLE, Class 1 |
|-----------|----------------------------|

## WIRED LAN

|          |                               |
|----------|-------------------------------|
| Ethernet | Support (w / Ethernet Cradle) |
|----------|-------------------------------|

## COMMUNICATION AND MESSAGING

|            |  |
|------------|--|
| VoIP / PTT |  |
|------------|--|

## DATA CAPTURE

|          |   |
|----------|---|
| Scanning | 1D&2D imager<br>Scan range (Code 39 barcode)<br>– 20 Mil : 2.0 inch to 30.0 inch<br>(5.08 cm to 76.2 cm)<br>– 4 Mil : 3.3 inch to 8.8 inch<br>(8.4 cm to 22.4 cm) |
| Camera   | Rear : 13MP Autofocus with<br>flash Front : 2MP Fixed Focus   |
| NFC      | (Optional)<br>ISO 14443 Type A and B; F;<br>FeliCa, and ISO 15693 cards, MiFare   |

## SENSOR

|               |  |
|---------------|--|
| Light Sensor  | Ambient Light                                    |
| Motion Sensor | Proximity, Gyroscope,<br>Accelerometer, Magnetic |

## USER ENVIRONMENT

|                               |  |
|-------------------------------|--|
| Operating Temp                | -10 ° C to 50 ° C / 14 ° F to 122 ° F  |
| Storage Temp                  | -40 ° C to 70 ° C / -40 ° F to 158 ° F   |
| Humidity                      | 95% non-condensing   |
| Drop Spec                     | Multiple 1.2m / 4 ft. drop to tile over concrete<br>at room temperature per MIL-STD 810G                     |
| Tumble Spec                   | 1000 1.6 ft. / 0.5 m tumbles;<br>meets and exceeds IEC tumble specification                                  |
| Sealing                       | IP67   |
| Vibration                     | 4 g' s PK Sine (5 Hz to 2 kHz); 0.04g2/Hz<br>Random (20 Hz to 2 kHz); 60 minute duration per<br>axis, 3 axis |
| Thermal Shock                 | -40° C to 70° C rapid transition   |
| Electrostatic Discharge (ESD) | +/-15kVdc air discharge+/-8kVdc direct<br>discharge+/-8kVdc indirect discharge                               |

\* Specification subject to change without notice